KUSAM-MECO®
An ISO 9001:2015 Company

5½ DIGIT BENCH TOP TRMS DIGITAL MULTIMETER MODEL - KM 3560

THINK SAFETY
THINK KUSAM-MECO®

SPECIAL FEATURES :

- Real 5½ digits readings resolution (119999 counts).
- 1 µV resolution
- True-RMS AC Voltage and AC Current measuring.
- 4.3-inch color LCD touch screen with double display for easy viewing.
- Two sets of input interfaces front and rear, which provides convenience to arrange wires.
- In addition to numerical data display, it also features histograms, trend charts, bar charts, and statistics functions.

NEW



Preliminary Data


FEATURES :

- Reading Rate : 500 reading/s;
- Auto Range
- Diode Continuity Test
- Trigger
- Save / read
- Math : MAX/MIN, Rel, dB, dBm, Limit, Statistic


Temperature Probe


Test Lead


Power cord


SOFTWARE CD

GENERAL SPECIFICATIONS :		
Functions	**Range**	**Accuracy**
DC Voltage	100mV / 1V / 10V / 100V / 1000V	± (0.012 + 0.005)
AC Voltage	100mV / 1V / 10V / 100V / 750V	± (0.2 + 0.1)
DC Current	100µA / 1mA / 10mA / 100mA / 1A / 10A	± (0.05 + 0.007)
AC Current	100µA / 1mA / 10mA / 100mA / 1A / 10A	± (0.5 + 0.1)
Resistance	100Ω / 1KΩ / 10KΩ / 100KΩ / 1MΩ / 10MΩ / 100MΩ	± (0.03 + 0.005)
Capacitance	1nF / 10nF / 100nF / 1µF / 10µF / 100µF	± (0.2 + 0.5)
Frequency	5Hz ~ 1MHz	± 0.02
Temperature	- 200°C ~ 800°C	± 0.2°C(without accuracy of probe)
Power Supply	115 V / 230 V, 50 Hz / 60 Hz, 15 VA	
Safety	IEC61010-1: 2001, CAT I 1000V / CAT II 600V, Class of pollution: 2	
Interface	USB Host, USB Device, RS-232, LAN, GBIP (optional)	
Dimension	Approx. 256 x 106 x 322 mm	
Weight	Approx. 3.5kg.	
Accessories	Power Cord :1, Test Lead Kit :1, Temperature Probe:1 CD (User's Guide + PC software) : 1	

All Specifications are subject to change without prior notice.

KUSAM-MECO®
An ISO 9001:2015 Company

Shop no.18, 1st Floor, CIDCO Shopping Complex, Plot # 9, Sector-7, Rajiv Gandhi Marg, Sanpada, Navi Mumbai - 400705. **Sales Direct :** +91-9867488006, 9867675093
Email : sales@kusam-meco.co.in **Web.:** www.kusamelectrical.com