

FEATURES :

- **Measurement Ranges:** 30A / 300A / 3000A AC
- **Output Sensitivity:** 100mV/10mV/1mV per Amp (AC Coupled)
- **18" flexible sensor fit around conductors up to 5.8" in diameter.**
- **8.5mm coil diameter allows measurement in tight spaces. (Double insulated)**
- **1.8m (6 ft) cable.**
- **Flashing LED low battery indicator.**
- **Dual banana plug termination for direct input into DMM.**
- **EN 61010, CAT IV 600V , CAT III 1000V.**

**ELECTRICAL SPECIFICATIONS :**

Measuring Ranges	30A / 300A / 3000A
Output Sensitivity	100mV/10mV/1mV per A (AC coupled)
Accuracy (45/65Hz)	±1% of full scale
Frequency Range	45 ~ 500Hz
Phase Error (45/65Hz)	< ±1°
Position Sensitivity	± 2.8% of full scale
Noise	0.03A / 0.075A / 0.5A
Low Battery	Indicated by a red LED
Power Indicate	Indicated by a green LED
Power Supply	1.5V AAA x 2 Alkaline battery
Dimension	Approx. 120(L) x 70(W) x 26(H) mm
Weight	Approx. 286gm.(including Battery)
Accessories	Battery, User Manual & carrying case.

Note: All Specification are Subject to change without prior notice.