

SPECIAL FEATURES :

- VFD-ACV & VFD-Hz;
- Display Hold w/Hold-alert™ warning;
- BeepLit™ Diode w/BeepPass™ indication;
- Relative-Zero mode;
- BeepJack™ audible & visible input warning
- Hi/Lo EF-Detection (NCV & Single pole);
- MAX Hold;
- BeepLit™ Continuity;
- Backlighted LCD display;



GENERAL SPECIFICATIONS :

- **Sensing:** True RMS sensing
- **Display:** 3-5/6 digits 6,000 counts
- **Update Rate:** 5 per second nominal
- **Operating Temperature:** -10°C to 50°C
- **Relative Humidity:** Maximum relative humidity 80% for temperature up to 31°C decreasing linearly to 50% relative humidity at 50°C
- **Altitude:** Operating below 2000m
- **Storage Temperature:** -20°C ~ 60°C, < 80% R.H. (with battery removed)
- **Temperature Coefficient:** Nominal 0.15 x (specified accuracy)/ °C @ (-10°C ~ 18°C or 28°C ~ 50°C), or otherwise specified
- **Low Battery:** Below approx. 2.5V
- **Power Supply:** 1.5V AAA Size battery X 2
- **Power Consumption (typical):** 3.2mA
- **APO Consumption (typical):** 10A
- **APO Timing:** Idle for approx. 32 minutes
- **Accessories:** Test lead set, User's manual, Banana-plug type-K thermocouple
- **Optional purchase accessories:** BKB32 banana-plug to type-K socket plug adaptor



Preliminary Data

SAFETY :

- Certified per IEC/UL/EN61010-1 Ed. 3.1, IEC/UL/EN61010-2-033 Ed. 2.0, IEC/UL/EN61010-031 Ed. 2.0 and the corresponding CAN/CSA-C22.2 regulations to Measurement Categories: CAT III 1000V and CAT IV 600V
- **Transient Protection:** 8.0kV (1.2/50μs surge)
- **Pollution Degree:** 2
- **E.M.C.:** Meets EN61326-1:2013
mV, Diode, Ohm, & Temperature; in an RF field of 1V/m:
Total Accuracy = Specified Accuracy + 100 digits
Other functions; in an RF field of 3V/m:
Total Accuracy = Specified Accuracy + 100 digits
- **Overload Protection:**
μA & mA: 0.63A/1000V DC/AC rms, IR 10kA, F fuse; or better
A: 11A/1000V DC/AC rms, IR 20kA, F fuse; or better
V: 1100V DC/AC rms
mV, Ohm, & others: 1000V DC/AC rms

ELECTRICAL SPECIFICATION

Accuracy is given as ± (% of reading digits + number of digits) or otherwise specified @ 23°C ± 5°C

AC Voltage & Current accuracies are specified from 1 % to 100 % of range or otherwise specified. Maximum Crest Factor <2:1 at full scale & <4:1 at half scale, and with signal component frequencies limited to the specified bandwidth of the AC functions for non-sinusoidal waveforms

AC VOLTAGE

RANGE	Accuracy
50Hz ~ 60Hz	
60.00mV ¹⁾ , 600.0mV ²⁾	1.0% + 3d
6.000V, 60.00V, 600.0V, 1000V	0.7% + 3d
45Hz ~ 500Hz	
60.00mV ¹⁾ , 600.0mV ²⁾	2.0% + 3d
6.000V, 60.00V, 600.0V, 1000V	2.0% + 3d
500Hz ~ 1kHz	
60.00mV ¹⁾ , 600.0mV ²⁾	2.0% + 3d
6.000V, 60.00V, 600.0V, 1000V	Unspecified

Input Impedance: 10M, 20pF nominal

¹⁾Signal peak absolute values, including DC bias, less than 130mV_{peak}

²⁾Signal peak absolute values, including DC bias, less than 1300mV_{peak}

VFD-ACV (with Low Pass Filter)

RANGE	Accuracy ¹⁾
10 ~ 100Hz	
600.0V, 1000V	1.0% + 3d
100 ~ 400Hz	
600.0V, 1000V	10.0% + 3d ²⁾

¹⁾Not specified for fundamental frequency > 400Hz

²⁾Accuracy linearly decreases from 1% + 3d @100Hz to 10% + 3d @400Hz

DC Voltage

RANGE	Accuracy
60.00mV, 600.0mV, 6.000V	0.3% + 2d
60.00V	0.4% + 2d
600.0V	0.2% + 2d
1000V	0.4% + 2d

Input Impedance: 10M, 20pF nominal

Note: All Specification are Subject to change without prior notice.

DC Current

RANGE	Accuracy	Burden Voltage
600.0μA, 6000μA	1.0% + 3d	0.1mV/μA
60.00mA, 600.0mA	0.7% + 3d	3.0mV/mA
6.000A, 10.00A ¹⁾		25mV/A

¹⁾10A continuous, >10A to 20A for 30 seconds max with 5 minutes cool down interval

AC Current

RANGE	Accuracy	Burden Voltage
50Hz ~ 500Hz		
600.0μA, 6000μA	1.5% + 3d	0.1mV/μA
60.00mA, 600.0mA	1.0% + 5d	3.0mV/mA
6.000A, 10.00A ¹⁾		25mV/A

¹⁾10A continuous, >10A to 20A for 30 seconds max with 5 minutes cool down interval

Ohm

RANGE ¹⁾	Accuracy
600.0Ω, 6.000kΩ	0.3% + 3d
60.00kΩ, 600.0kΩ	0.5% + 3d
6.000MΩ ²⁾ , 60.00MΩ ³⁾	0.9% + 2d ⁴⁾

¹⁾Open Circuit Voltage: 1.6VDC typical

²⁾Constant Test Current: 0.2A Typical

³⁾Constant Test Current: 0.02A Typical

⁴⁾5%+20d @ >30M

Capacitance

RANGE	Accuracy
20.00nF, 200.0nF	1.5% + 8d
2000nF	1.5% + 3d
20.00μF, 200.0μF, 2000μF	

Accuracies with film capacitor or better

Logic Frequency

Range	Sensitivity (Squarewave)
5.00Hz ~ 300.0kHz	3Vpeak

Accuracy: 0.03% + 4d

Line Frequency

Function	Sensitivity (Sine RMS)	Range
6V	5V	10Hz-50kHz
60V	10V	10Hz-50kHz
600V	50V	10Hz-1kHz
1000V	500V	50Hz-1kHz
VFD 60V	50V	10Hz-1kHz
VFD 100V	500V	50Hz-1kHz
600μA, 6000μA	500μA	10Hz-5kHz
60mA, 600mA	50mA	10Hz-5kHz
6A, 10A	8A	50Hz-1kHz

Accuracy: 0.03% + 4d

BeepLit™ Continuity Tester

Continuity Threshold: Between 30 and 480

Continuity ON Response Time: <15ms

Audible Indication: Beep sound

Visible Indication: LCD Backlight

BeepLit™ Diode Tester

RANGE	Accuracy	Test Current (Typical)	Open Circuit Voltage
3.0000V	0.9% + 2d	0.3mA	<3.2 VDC

Temperature

RANGE	Accuracy ^{1) 2)}
-40.0°C ~ 0.0°C	1% + 2°C
0.0°C ~ 99.9°C	1% + 1°C
100°C ~ 400°C	
-40.0°F ~ 32.0°F	1% + 4°F
32.0°F ~ 99.9°F	1% + 2°F
100°F ~ 752°F	

°F selection can be left out as factory calibration default for countries that only accept metric units

¹⁾Accuracies assume the meter interior and the ambient have reached the same temperature (isothermal stage) for a correct junction voltage compensation. Allow enough settling time for a significant change in ambient temperature. It can take up to an hour for changes > 5°C

²⁾Type-K thermocouple range & accuracy not included

Non-Contact EF-Detection

Bar-segment Indication	EF-H (Hi Sensitivity)	EF-L (Lo Sensitivity)
	Typical Voltage (Tolerance)	
-	15V (3V ~ 30V)	70V (30V ~ 120V)
--	30V (10V ~ 60V)	140V (60V ~ 240V)
---	60V (20V ~ 120V)	280V (120V ~ 480V)
----	120V (40V ~ 240V)	560V (240V ~ 960V)
-----	240V (>80V)	1000V (>900V)

Indication: Display bar-segments, backlight flashing, & beep tones in proportion to the field strength

Detection Frequency: 50/60Hz

Detection Antenna: Top end center of the meter

Probe-Contact EF-Detection: For more precise indications of live wires, such as distinguishing between live and ground connections, use direct contact testing with one single test-probe via the input terminal COM or V. The COM terminal (Black) has the best sensitivity.

Note: All Specification are Subject to change without prior notice.



Shop no.18, 1st Floor, CIDCO Shopping Complex, Plot # 9, Sector-7, Rajiv Gandhi Marg, Sanpada, Navi Mumbai - 400705.

Email : sales@kusam-meco.co.in

Sales Direct : +91-9867488006, 9867675093

Website : www.kusamelectrical.com